
metalphoto[®]

DRILLING SYSTEMS



THE TECHNOLOGY :

ANODIZED LAYER The glass-clear, sapphire-hard anodized laver resists chemicals, paint, abrasion and dirt.



ALUMINUM LAYER The rigid aluminum base won't peel, crack or delaminate.

SEALED IMAGE The image is absorbed into the pores.





Machine **Control Panels**

EXCEPTIONALLY DURABLE. WIDELY SPECIFIED. **ALWAYS READABLE.**

For over 50 years, industrial and military engineers have specified Metalphoto photosensitive anodized aluminum for durable nameplates, barcode labels, service schematics and control panels installed in harsh operating environments. Metalphoto's proprietary technology permanently seals a UV-stable image inside of anodized aluminum, offering the confidence of unparalleled durability, image resolution and barcode readability.

On-shore and off-shore oilfield drilling equipment must survive challenging environmental and operating conditions. Metalphoto offers the confidence of lasting readability for regulatory, financial and maintenance compliance. Whether a calibration tag, chemical/salt spray resistant barcode label or custom machine control panel, Metalphoto is designed to survive harsh oilfield operating conditions.

Contact Photo-Graphics Co., Inc. to get Metalphoto specified into your designs.

PRODUCT BENEFITS

EXCEPTIONALLY DURABLE:

- + UV-stable image is permanently sealed within the anodized aluminum.
- + Virtually impervious to chemicals, heat, abrasion, salt spray and sunlight.
- + Certified for 20 year plus outdoor applications.
- + Earned more top scores than any other IUID barcode label material tested by the U.S. Navy (NSWC, Corona Division, IUID Center; August 2011).

WIDELY SPECIFIED:

- + Meets a wide array of commercial, government and military specifications.
- Notable certifications include: MIL-STD-130N, STANAG 2290, GGP-455B(3) Type I, MIL-DTL-15024F, MIL-P-19834B and A-A-50271.

PHOTOGRAPHIC RESOLUTION:

- Photographic image affords extreme detail and contrast at any size. +
 - Anti-counterfeit security printing is available.

Photo-Graphics Co., Inc. 6633 Intercal Way Prescott, AZ 86301 USA

T: 816-761-3333 F: 816-761-3032

Email: sales@pgnameplates.com www.nameplates-labels.com

metalphoto[®]

PERFORMANCE CHARACTERISTICS

Because of its ability to perform across a range of challenging environments, Metalphoto meets an array of government, industrial and military specifications. Visit **www.nameplates-labels.com** for a list of specifications for which Metalphoto is qualified.

C H A R A C T E R I S T I C	RESULT
Abrasion Resistance	No pronounced image loss, degradation or reduced readability after 7,000 cycles on an abrading wheel.
Acid Corrosion	No deterioration or image degradation after 24 hours in 3% nitric acid.
Heat Resistance	No legibility loss or degradation when subjected to 1,000°F.
Salt Spray Corrosion	No deleterious effect after a 720-hr salt spray (fog) test. 2,6 "Very Good" corrosion resistance after 113 days seawater exposure.
Accelerated Light and Weather Resistance	No pronounced deterioration of legibility after 400-hr carbon arc weatherometer exposure. (\approx 20+ year outdoor life)
Accelerated Oxygen Aging	No discoloration or fading after 96-hr/300 psi/ 70°C oxygen bomb aging
Stain Resistance	No black fading when plates are exposed to tincture of iodine.
Cleaning Resistance	No deleterious effects when tested with alkaline cleaners (MILC- 87937 or equivalent) for aircraft surfaces.
Low Temperature Resistance	No deleterious effect or image fade after 1 hour at -50°F. No impairment of legibility upon exposure at -67°F.
Organic Solvent Resistance	No softening, staining or noticeable fade after 24-hr exposure to: JP-4 fuel, Gasoline, Mineral Spirits, Methyl Ethyl Ketone, Turpentine, Turbine & Jet Fuel, Kerosene, Xylol, Acetone, Toluol, Heptane, Trichlorethylene, MIL-H-5606 Hydraulic Fluid and MIL-L-7808 Jet Engine Oil.
Fungus Resistance	Visual reading of "0" per ASTM-G21.
Thermal Shock	No deterioration after 3 cycles between -65°C and 125°C
Moisture Resistance	No deterioration after 10 humidity cycles per MIL-STD-202, method 106.

TECHNICAL SPECIFICATIONS

MATERIAL: Anodized Aluminum Sheets

SIZES: 10"x 12", 12"x 20"

THICKNESSES: .003", .005", .008", .012", .020", .032", .039", .063" FINISHES:



MATTE non-reflective with dull finish



SATIN semi-gloss medium reflective material

TO ORDER

Call 816-761-3333 or visit our website at www.nameplates-labels.com

Photo-Graphics Co., Inc. does not warrant the performance of its materials in any environment. Metalphoto is a registered trademark of Horizons Incorporated.

Photo-Graphics Co., Inc. 6633 Intercal Way Prescott, AZ 86301 USA

T: 816-761-3333 F: 816-761-3032

Email: sales@pgnameplates.com www.nameplates-labels.com